



M4 style office partition

M4 款办公屏风

畅润的质感，细致的拼接，都反映出精益求精的工艺和一丝不苟的态度。

Smooth texture and delicate joining together, all reflect the excelsior craft and meticulous attitude.

专利产品，仿冒必究。



M4 office partition for 4 person
M4 四人位



M4 office partition for 3 person

M4 三人位

M4 style office partition

M4 款办公屏风

以鲜明活泼的色调彰显出办公空间的个性和品味，诠释出新时代的都市办公理念。













In lively tonal reflect the personality and taste of office space, interprets the new era of urban office concept.

专利产品，仿冒必究。



CM4001 A 柱上盖 A pole cover	CM4013 弧形 A 柱上盖 Arc A pole cover	CM4002 落差 A 柱上盖 higher and lower A pole cover	CM4003 A 柱底座 A pole base
CM4014 无顶杆 A 柱上盖 A pole cover without top pole	CM4015 无顶杆落差 A 柱上盖 higher and lower A pole cover without top pole	CM4004 转角柱上盖 connection pole cover	CM4005 转角柱底座 connection pole base
CM4011 三向柱上盖 cover for 120 degree way	CM4012 三向柱底座 base for 120 degree way	CM6506 M4 转 M6 上盖 M4-M6 connection cover	CM6507 M4 转 M6 底座 M4-M6 connection base
CM2045 M2 转 M4 上盖 M2-M4 connection cover	CM2046 M2 转 M4 底座 M2-M4 connection base	CM4010 一字连接片 straight connection piece	CM4009 屏风连接片 connector piece

CM4007 简易线盒加固  cable fixture for K4809	CM4008 线盒加固  cable fixture for K4807	CM4006 玻璃框角码  hinge for glass frame	IP25 台板托片  panel supporter
CM4520 M8 调节脚  screw for M8			

K4800 A 柱 / 顶杆  A pole/top pole T=1.4mm R=0.25kg/m	K4801 顶 / 侧封边  top/side seal T=1.2mm R=0.15kg/m	K4802 大玻璃框  big glass frame T=0.8mm R=0.30kg/m	K4803 小玻璃框  little glass frame T=0.8mm R=0.13kg/m
K4804 小中杆  little mid pole T=0.8mm R=0.16kg/m	K4805 大中杆  middle pole T=0.8mm R=0.30kg/m	K4806 线盒杆  wiring box pole T=0.8mm R=0.32kg/m	K4807 线盒板  wiring box cover T=1.0mm R=0.41kg/m
K4809 简易线盒板  wiring box for easy fixture T=0.9mm R=0.39kg/m	K4810 转角柱  connection pole T=0.9mm R=0.48kg/m	K4811 三向转角柱  3 way connection pole T=1.0mm R=0.34kg/m	K4851 M2 转 M4 柱  M2-M4 connection pole T=0.8mm R=0.31kg/m